

SKF 2209 EKTN9 self aligning ball bearings

SKF 2209 EKTN9 self aligning ball bearings 130 mm Da Needs Analysis , Manufacturing Service . Get Your 60.325 mm da Free.

da	60.325 mm
Da	130 mm
Ca	37.008 mm
A1	79.375 mm
A2	120.65 mm
S	3.175 mm
ba	32.544 mm
H	161.925 mm
H1	82.55 mm
H2	30.163 mm
J min.	219.075 mm
J max.	244.475 mm
J1	47.625 mm
L	285.75 mm
N1	15.875 mm
R1	46.038 mm
R2	21.431 mm
RG	1/4 NPT
PG	1/8 NPT
h	28.575 mm
Housing	FSAFS 515
Bearing	22215 EK
Adapter sleeve assembly	SNW 15×2.3/8

Stabilizing ring	SR-15-0
Labyrinth ring	2 x LOR 36
End plug (suffix Y)	EPR 7
Bearing limiting speed	6300 r/min
P60°	75.6 kN
P90°	45.4 kN
P120°	28.5 kN
P150°	25.4 kN
P180°	30.7 kN
Pa	6.94 kN
Mass pillow block	15.4 kg
Cap bolt	2 x 1/2-13 UNC
Cap bolt recommended tightening torque	149.1 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.5 in
Initial grease fill	68.04 g