

# SKF 230/1060 CAKF/W33 + OH 30/1060 H tapered roller bearings

SKF 230/1060 CAKF/W33 + OH 30/1060 H tapered roller bearings  
0.0 Inventory Industries and Applications ? We sell discount online as well as cheap machinery parts.

Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	74 lb
EAN	0013992041012
Product Group	B04144
Number of Mounting Holes	2
Mounting Method	Clamp Collar
Housing Style	2 Bolt Pillow Block
Rolling Element	Cylindrical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Expansion
Mounting Bolts	24 Millimeter
Relubricatable	Yes
Insert Part Number	LSE315BX
Seals	Triple Lip Labyrinth
Housing Configuration	2 Piece Split
Inch – Metric	Inch
Other Features	Single Row   Light Duty   With Support   Wide Inner Ring
UNSPSC	31171511

Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Pillow Block
Weight / LBS	62.79
Nominal Bolt Center to Center	13.9 Inch   354 Millimeter
Actual Bolt Center to Center	13.9 Inch   354Millimeter
Bolt Spacing Maximum	0 Inch   0Millimeter
d	3.938 Inch   100.025 Millimeter
B	4.921 Inch   125 Millimeter
D	3.346 Inch   85 Millimeter
Bolt Spacing Minimum	0 Inch   0Millimeter
Shaft Size	3-15/16 in
Seal Type	Aluminium Triple Labyrinth
Bearing Type	Split Cylindrical Expansion Type
Support Type	Two-Bolt Plummer Block
Series Type	Light Series
Pillow/Plummer Block Style	Split Cylindrical Housed Unit – Standard
Bolt Size	2 x M24
Dimension H	4.921 in
Dimension H1	2.0 in
Dimension H2	10.7 in
Dimension J	13.9 in
Dimension L	16.5 in
Dimension M	4.0 in
Housing Width	5.3 in
Cr – Dynamic Load Rating	64745 lbf
Cor – Static Load Rating	82280 lbf

Maximum Speed	2340 rpm
Note	This product line was formerly known as “Revolvo”