

SKF 230/900 CAK/W33 tapered roller bearings

Can't find what you're looking for SKF 230/900 CAK/W33 tapered roller bearings ? Our expert Representatives be in contact with you 73.025 mm da shortly! 69.799 mm Ca

da	73.025 mm
Da	180 mm
Ca	69.799 mm
A1	111.125 mm
A2	171.45 mm
ba	52.388 mm
H	222.25 mm
H1	114.3 mm
H2	44.45 mm
J min.	295.275 mm
J max.	333.375 mm
J1	60.325 mm
L	387.35 mm
N1	22.225 mm
R1	66.675 mm
R2	30.163 mm
RG	3/8 NPT
PG	1/4 NPT
h	47.625 mm
Housing	FSAF 617
Bearing	1317 K
Adapter sleeve assembly	SNW 117×2.7/8

Stabilizing ring	2 x SR-1617
Labyrinth ring	2 x LOR 183
PosiTrac Plus contact element	2 x B10724-184
End plug (suffix Y)	EPR 10
Max. speed for PosiTrac Plus seal	1950 r/min
P60°	104 kN
P90°	62.3 kN
P120°	39.1 kN
P150°	35.6 kN
P180°	42.9 kN
Pa	10.5 kN
Mass pillow block	25.5 kg
Cap bolt	2 x 3/4-10 UNC
Cap bolt recommended tightening torque	515.2 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.75 in
Initial grease fill	365.71 g