

# SKF 23032 CCK/W33 spherical roller bearings

SKF 23032 CCK/W33 spherical roller bearings SEARCH – Whether it's agriculture or 30 Bore Diameter (mm) construction 30x80x100 Size (mm) equipment your working on, Has the you need.

Size (mm)	30x80x100
Bore Diameter (mm)	30
Outer Diameter (mm)	80
Width (mm)	100
D	80 mm
d	30 mm
B	100 mm
C	35 mm
B1	63 mm
B2	15 mm
C1	1 mm
d1	47 mm
G	M 30×1.5
G1	32 mm
M	8 mm
M1	4 mm
SW	14 mm
r <sub>1,2</sub> – min.	1.1 mm
Basic dynamic load rating – C	69.3 kN
Basic static load rating – C0	86.5 kN
Fatigue load limit – Pu	10.8 kN

Maximum dynamic radial loads – Fr	48 kN
Maximum static radial loads – F0r	69.5 kN
Limiting speed	1900 r/min
Mass support roller	1.6 kg
Recommended tightening torque	450 N·m
Grease fitting	NIP A3x9.5
Hexagonal nut	M 30x1.5
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	1.854
EAN	7316570936209
Product Group	B04144
Roller Surface Profile	Flat
Profile	Stud Type
Thread Size	M30X1.5
Stud Profile	Standard Stud
Enclosure	Sealed
Rolling Element	Cylindrical Roller Bearing – Double Row
Relubricatable	Yes
Hex Socket	Yes
Inch – Metric	Metric
Other Features	Full Complement   Labyrinth Seal
Long Description	80MM Roller Diameter; 35MM Roller Width; Flat Roller Surface; Stud Type; 30MM Stud Diameter; M30X1.5
UNSPSC	31171530

Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Keyword String	Cam Follower
Manufacturer Item Number	NUKR 80 XA
Weight / LBS	3.527
Stud Diameter	1.181 Inch   30 Millimeter
Roller Width	1.378 Inch   35 Millimeter
Roller Diameter	3.15 Inch   80 Millimeter
r1,2 min.	1.1 mm
Basic dynamic load rating C	69.3 kN
Basic static load rating C0	86.5 kN
Fatigue load limit Pu	10.8 kN
Maximum dynamic radial loads Fr max.	48 kN
Maximum static radial loads F0r max.	69.5 kN
Mass cam follower	1.6 kg
Lubrication adapter	AP 14