

SKF 2307E-2RS1KTN9+H2307E self aligning ball bearings

170 Million used SKF 2307E-2RS1KTN9+H2307E self aligning ball bearings instantly searchable. Shop our large selection of parts based 8 Days Days to Ship on brand, price, description, and location. Order the with stock ...

| | |
|------------------------------|---------------|
| Days to Ship | 8 Days |
| Inner/Outer Ring Material | [Steel] Steel |
| Bearing Style | Open Type |
| Outer Ring Shape | Flat |
| Precision | Grade 0 |
| I.D.(Ø) | 70 |
| Rolling Element Material | [Steel] Steel |
| Retainer Type | No |
| Clearance sign | C3 |
| Accuracy(Class) | Class 0 |
| Acoustic Symbol | No |
| Holder Symbol | No |
| Symbol of Bearing Ring Shape | No |
| Seal, Shield Symbols | No |
| Precision Grade Symbol | No |
| Special Configurations Code | No |
| Rubugado Symbol | No |
| Material Symbol | No |
| Spacer, Sleeve symbol | No |
| Types | No |
| Type | Ball |

| | |
|------------------------------|-----------------|
| Specifications, Environment | Standard |
| Load Direction | Radial |
| Outer Ring | With Outer Ring |
| Number of Raceway Ring Rows | Single Row |
| Size Standards | Metric System |
| Combination symbol | No |
| Low Torque Specification | No |
| Internal Symbol | No |
| Torque Symbol | No |
| RoHS | 6 |
| d | 70 |
| D | 180 |
| B | 42 |
| Basic Dynamic Load Rating(N) | 128000 |
| Max. Allowed rpm(rpm) | 4100 |
| Specifications/Environment | Standard |
| Preload Mark | C3 |