

SKF 238/850 CAMA/W20 spherical roller bearings

SKF 238/850 CAMA/W20 spherical roller bearings manufacturer and global supplier of reliable ball and roller ... SKF 238/850 CAMA/W20 spherical roller bearings Industries Products Manufacturing & Engineering and Agricultural Bearings designed 0.0 Inventory to meet the unique requirements of our targeted industries.

Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	14 lb
EAN	0053893778181
Product Group	M06288
Component Description	Take Up Bearing Only
Rolling Element	Tapered Roller Bearing
Housing Style	Unit Only – Half Round Top Angle
Mounting Method	Concentric Collar
Compatible Take Up Frame	Not Specified
Adjustment Travel Length	0
Housing Material	Cast Iron
Other Features	Double Row Double Collar Two Lip Seal Electrodeposition Coating With Set Screw
Inch – Metric	Inch
Long Description	Take Up Bearing Only; 1-3/4" Bore; Tapered Roller Bearing; Unit Only – Half Round Top Angle; Co

UNSPSC	31171533
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Take Up
Manufacturer Item Number	E-TTU-TRB-1 3/4
Weight / LBS	14.29
Slot to Slot Distance	0 Inch 0 Millimeter
d	1.75 Inch 44.45 Millimeter
Slot Width	0 Inch 0 Millimeter
Shaft Size	1.75 in
Shaft Size Type	Imperial
UPC Code	053893778181
Dimension B	3-1/2 in
Dimension H	6-3/8 in
Dimension H1	5-3/16 in
Dimension H2	2.39 in
Dimension d1	3-7/16 in
Dimension A	1-3/4 in
Dimension A1	1-3/4 in
Housing Width	2-9/16 in
Dimension L	6-1/2 in
Dimension L1	6 in
Dimension L2	3.4 in
e	0.33
X (if $F_a/F_r \leq e$)	0.87
Y (if $F_a/F_r \leq e$)	2.64
X (if $F_a/F_r > e$)	0.7
Y (if $F_a/F_r > e$)	3.18
K Factor	1.83

C90 Dynamic Load Rating ¹	10300 lb
C0 Static Load Rating	43000 lb
Fa-max Maximum Permissible Thrust Load ²	2590 lb
Fr-max Maximum Allowable Slip Fit Radial Load ³	8400 lb
Max. Speed ⁴	3050 rpm
Note	Note: All units have a 1/8 pipe thread grease fitting The Maximum Permissible Thrust Load applies to