

SKF 24056 CCK30/W33 + A0H 24056 G tapered roller bearings

SKF 24056 CCK30/W33 + A0H 24056 G tapered roller bearings manufacturer and global supplier of 20 mm d reliable ball and roller ... SKF 24056 CCK30/W33 + A0H 24056 G tapered roller bearings Industries Products Manufacturing & Engineering and Agricultural Bearings designed to meet the 14 mm B unique requirements of our targeted industries.

d	20 mm
D	47 mm
B	14 mm
E	41.5 mm
F	26.5 mm
d1	29.7 mm
rs min	1 mm
r1s min	0.6 mm
Radial clearance class	CN
Mass (without HJ ring)	0.11 kg
Dynamic load, C	26.6 kN
Static load, C0	23.8 kN
Fatigue limit load, Cu	2.9 kN
Nref	13,000 rpm
Nlim	19,000 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.39 Hz

Characteristic rolling element frequency, BSF	4.31 Hz
Characteristic outer ring frequency, BPF ₀	4.68 Hz
Characteristic inner ring frequency, BRFI	7.32 Hz
da min	25 mm
Da max	43 mm
Db min	42 mm
Dc max	39 mm
ra max	1 mm
r1a max	0.6 mm