

SKF 30311J2/Q tapered roller bearings

High Quality SKF 30311J2/Q tapered roller bearings. Competitive 32x12x10 Size (mm) Pricing. Accept Small 32 Bore Diameter (mm) Order. Easy and Fast Shipping.

Size (mm)	32x12x10
Bore Diameter (mm)	32
Outer Diameter (mm)	12
Width (mm)	10
d	12 mm
D	32 mm
B	10 mm
d1	18.5 mm
D2	27.95 mm
r1,2 – min.	0.6 mm
da – min.	16 mm
da – max.	18 mm
Da – max.	28.5 mm
ra – max.	0.6 mm
Basic dynamic load rating – C	5.7 kN
Basic static load rating – C0	3 kN
Fatigue load limit – Pu	0.127 kN
Limiting speed	15000 r/min
Calculation factor – kr	0.03
Calculation factor – f0	12
Inventory	0.0
Manufacturer Name	SKF

Minimum Buy Quantity	N/A
Weight / Kilogram	0.034
EAN	7316570817461
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Stainless Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	12MM Bore; 32MM Outside Diameter; 10MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No
Other Features	Deep Groove NBR Seal
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	W 6201-2RS1
Weight / LBS	0.087
Outside Diameter	1.26 Inch 32 Millimeter
Bore	0.472 Inch 12 Millimeter
Outer Race Width	0.394 Inch 10 Millimeter
Inner Race Width	0 Inch 0 Millimeter
d1 ≈	18.5 mm

D2 ≈	27.95 mm
r _{1,2} min.	0.6 mm
d _a min.	16 mm
d _a max.	18 mm
D _a max.	28.5 mm
r _a max.	0.6 mm
Basic dynamic load rating C	5.72 kN
Basic static load rating C ₀	3 kN
Fatigue load limit P _u	0.127 kN
Calculation factor k _r	0.03
Calculation factor f ₀	12
Mass bearing	0.036 kg