

# SKF 306708 D deep groove ball bearings

Online shopping SKF 306708 D deep groove ball bearings from a 60 Bore Diameter (mm) great selection at Store. ... 60x78x10 Size (mm) Accessories.

Size (mm)	60x78x10
Bore Diameter (mm)	60
Outer Diameter (mm)	78
Width (mm)	10
d	60 mm
D	78 mm
B	10 mm
C	10 mm
r min.	0,3 mm
da min.	62 mm
da max	64,5 mm
Da max.	76 mm
ra max.	0,3 mm
Weight	0,106 Kg
Basic dynamic load rating (C)	11,5 kN
Basic static load rating (C0)	10,6 kN
(Grease) Lubrication Speed	8 000 r/min
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	4547359585926

Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Non-Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	60MM Bore; 78MM Outside Diameter; 10MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No
Other Features	Deep Groove   Non-Friction Nitrile Rubber Seal   Shell Alvania Prelubricated
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.225
Bore	2.362 Inch   60 Millimeter
Outside Diameter	3.071 Inch   78 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Outer Race Width	0.394 Inch   10 Millimeter
bore diameter:	60 mm
precision rating:	ISO Class 0
outside diameter:	78 mm

finish/coating:	Uncoated
overall width:	10 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Double Sealed
inner ring width:	10 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	10 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	8000 rpm
internal clearance:	CN
fillet radius:	0.3 mm
operating temperature range:	-40 to 120 °C
maximum rpm:	9400 RPM
dynamic load capacity:	11500 N
series:	68
static load capacity:	10600 N
manufacturer product page:	<a href="#">Click here</a>