

SKF 32052 X tapered roller bearings

Enjoy 177.8 mm db 153.988 mm dc High 160 mm da Margins on Competitive Pricing.Great Wholesale Products at Low Costs.

da	160 mm
db	177.8 mm
dc	153.988 mm
Da	287.459 mm
Ca	113.817 mm
A1	158.75 mm
A2	288.925 mm
S	4.763 mm
ba	82.55 mm
H	338.137 mm
H1	169.875 mm
H2	66.675 mm
J min.	441.325 mm
J max.	488.95 mm
J1	95.25 mm
L	558.8 mm
N1	28.575 mm
R1	104.775 mm
R2	49.212 mm
RG	3/4 NPT
PG	1/4 NPT
h	52.388 mm
Housing	SAW 232

Bearing	23232 CC/W33
Lock nut	AN 32
Lock washer	W 32
Stabilizing ring	SR-32-0
Taconite seal (db shaft position)	TER 156
Taconite seal (dc shaft position)	TER 142
End plug (suffix Y)	EPR 18
Max. speed for Taconite seal	440 r/min
P60°	226 kN
P90°	136 kN
P120°	85.9 kN
P150°	78.3 kN
P180°	94.3 kN
Pa	49.8 kN
Mass pillow block	111 kg
Cap bolt	4 x 3/4-10 UNC
Cap bolt recommended tightening torque	359.3 N·m
Cap bolt, SAE grade	5
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1 in
Initial grease fill	793.8 g