

SKF 331933/Q tapered roller bearings

are N/A Minimum Buy Quantity a few brands 0.0 Inventory you will find in our inventory. Find SKF 331933/Q tapered roller bearings to see what's in stock!

| | |
|---------------------------|--|
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 9.53 |
| EAN | 7316576675034 |
| Product Group | M06288 |
| Number of Mounting Holes | 2 |
| Mounting Method | Concentric Collar |
| Housing Style | 2 Bolt Pillow Block |
| Rolling Element | Spherical Roller Bearing |
| Housing Material | Cast Iron |
| Expansion / Non-expansion | Expansion |
| Mounting Bolts | 3/4 Inch |
| Relubricatable | Yes |
| Insert Part Number | 22215 |
| Seals | Garter Spring |
| Housing Configuration | 1 Piece Solid |
| Inch – Metric | Inch |
| Other Features | Double Row Heavy Duty Open End With Set Screw |
| Long Description | 2 Bolt Pillow Block; 3" Bore; 3-1/4" Base to Center Height; Concentric Collar Mount; Spher |

| | |
|-------------------------------|--------------------------------|
| UNSPSC | 31171511 |
| Harmonized Tariff Code | 8483.20.40.80 |
| Noun | Bearing |
| Keyword String | Pillow Block |
| Manufacturer Item Number | SYR 3-3 |
| Weight / LBS | 21 |
| B | 92.075 mm |
| Bolt Spacing Minimum | 7.813 Inch 198.44Millimeter |
| Nominal Bolt Center to Center | 8.1 Inch 206.4 Millimeter |
| d | 3 Inch 76.2 Millimeter |
| Actual Bolt Center to Center | 0 Inch 0Millimeter |
| D | 3.625 Inch 92.075 Millimeter |
| Bolt Spacing Maximum | 8.438 Inch 214.325Millimeter |
| bore diameter: | 3.0000 in |
| bolt center-to-center length: | 206.375 mm |
| overall length: | 10.4375 in |
| base width: | 65.1 mm |
| overall height: | 6.4375 in |
| expansion type: | Expansion Bearing (Floating) |
| mounting: | Two-Bolt Base |
| finish/coating: | Uncoated |
| bearing type: | Spherical Roller |
| overall width: | 3-5/8 in |
| bore type: | Round |
| seal type: | Contact/Lip |
| housing construction: | Solid Pillow Block |
| radial dynamic load capacity: | 158 kN |
| base to bore centerline: | 3.2500 in |
| radial static load capacity: | 208 kN |

| | |
|-----------------------------|---------------------|
| duty type: | Standard Duty |
| lubrication type: | Lubrication Fitting |
| housing material: | Cast Iron |
| series: | SYR |
| locking device: | Set Screw |
| replacement bearing: | 22215 |
| da | 76.2 mm |
| d2 | 111.125 mm |
| A | 68.263 mm |
| A1 | 95.25 mm |
| H | 165.894 mm |
| H1 | 82.55 mm |
| H2 | 57.15 mm |
| L | 265.113 mm |
| J max. | 223.838 mm |
| J min. | 198.438 mm |
| s | 31.75 mm |
| S | 0.794 mm |
| Basic dynamic load rating C | 158 kN |
| Limiting speed | 950 r/min |
| Mass bearing unit | 9.53 kg |
| Attachment bolt diameter G | 19.05 mm |