

# SKF 6003-2RSL deep groove ball bearings

Request A Quote For Your 0.0 Inventory Special SKF 6003-2RSL deep groove ball bearings Needs Today! Free Quotes. ISO 9001 certified.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 22.7   |
| EAN                       | 0883450229913  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | V Lock   |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 20 Millimeter  |
| Relubricatable            | Yes  |
| Insert Part Number        | 22219  |
| Seals                     | Triple Lip Urethane  |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Inch   |
| Other Features            | Double Row   Single Nut   SN Style   |
| Long Description          | 2 Bolt Pillow Block; 3-3/16" Bore; 3-15/16" Base to Center Height; V Lock Mount; Spherical |

|                               |                                 |
|-------------------------------|---------------------------------|
| UNSPSC                        | 31171511                        |
| Harmonized Tariff Code        | 8483.20.40.80                   |
| Noun                          | Bearing                         |
| Keyword String                | Pillow Block                    |
| Manufacturer Item Number      | QVSN19V303S0                    |
| Weight / LBS                  | 50                              |
| B                             | 3.938 Inch   100.025 Millimeter |
| d                             | 3.188 Inch   80.975 Millimeter  |
| Bolt Spacing Minimum          | 11.024 Inch   280Millimeter     |
| Nominal Bolt Center to Center | 11.2 Inch   285.5 Millimeter    |
| D                             | 3.661 Inch   93 Millimeter      |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter            |
| Bolt Spacing Maximum          | 11.496 Inch   292Millimeter     |