SKF 6008/HR11QN deep groove ball bearings

Manufacturers of all are represented in 0.3125 in d our partial list of clients. Contact Gary for a complete SKF 6008/HR11QN deep groove ball bearings list of clients and projects.

d0.3125 inradial static load capacity:8410 lbfmisalignment angle:7 °operating temperature range:Max 250 °Fshank thread length:0.7500 inhead diameter:0.8750 inrod end type:Female Threadedhead width:0.3440 inshank thread size:5/16-24ball width:0.4370 inthread direction:Right Handlength to ball center:1.3750 ingrade:Precision Extra Capacityoverall height:1.8130 inthread type:Spherco®lubrication type:Non-Lubricatablemanufacturer product page:Click herehousing material:0.08 lbsball material:52100 Alloy Steel		
misalignment angle: 7 ° operating temperature range: Max 250 °F shank thread length: 0.7500 in head diameter: 0.8750 in rod end type: Female Threaded head width: 0.3440 in shank thread size: 5/16-24 ball width: 0.4370 in thread direction: Right Hand length to ball center: 1.3750 in grade: Precision Extra Capacity overall height: 1.8130 in thread type: UNF-3B series: Spherco® lubrication type: Non-Lubricatable manufacturer product page: Click here housing material: 4130 or 4340 Alloy Steel Weight 0.08 lbs	d	0.3125 in
operating temperature range:Max 250 °Fshank thread length:0.7500 inhead diameter:0.8750 inrod end type:Female Threadedhead width:0.3440 inshank thread size:5/16-24ball width:0.4370 inthread direction:Right Handlength to ball center:1.3750 ingrade:Precision Extra Capacityoverall height:1.8130 inthread type:Spherco®lubrication type:Non-Lubricatablemanufacturer product page:Click herehousing material:4130 or 4340 Alloy SteelWeight0.08 lbs	radial static load capacity:	8410 lbf
shank thread length: 0.7500 in head diameter: 0.8750 in rod end type: Female Threaded head width: 0.3440 in shank thread size: 5/16-24 ball width: 0.4370 in thread direction: Right Hand length to ball center: 1.3750 in grade: Precision Extra Capacity overall height: 1.8130 in thread type: UNF-3B series: Spherco® lubrication type: Non-Lubricatable manufacturer product page: Click here housing material: 4130 or 4340 Alloy Steel Weight 0.08 lbs	misalignment angle:	7°
head diameter:0.8750 inrod end type:Female Threadedhead width:0.3440 inshank thread size:5/16-24ball width:0.4370 inthread direction:Right Handlength to ball center:1.3750 ingrade:Precision Extra Capacityoverall height:1.8130 inthread type:UNF-3Bseries:Spherco®lubrication type:Non-Lubricatablemanufacturer product page:Click herehousing material:4130 or 4340 Alloy Steel	operating temperature range:	Max 250 °F
rod end type: Female Threaded head width: 0.3440 in shank thread size: 5/16-24 ball width: 0.4370 in thread direction: Right Hand length to ball center: 1.3750 in grade: Precision Extra Capacity overall height: 1.8130 in thread type: UNF-3B series: Spherco® lubrication type: Non-Lubricatable manufacturer product page: Click here housing material: 4130 or 4340 Alloy Steel Weight 0.08 lbs	shank thread length:	0.7500 in
head width:0.3440 inshank thread size:5/16-24ball width:0.4370 inthread direction:Right Handlength to ball center:1.3750 ingrade:Precision Extra Capacityoverall height:1.8130 inthread type:UNF-3Bseries:Spherco®lubrication type:Non-Lubricatablemanufacturer product page:Click herehousing material:4130 or 4340 Alloy Steel	head diameter:	0.8750 in
shank thread size: 5/16-24 ball width: 0.4370 in thread direction: Right Hand length to ball center: 1.3750 in grade: Precision Extra Capacity overall height: 1.8130 in thread type: UNF-3B series: Spherco® lubrication type: Non-Lubricatable manufacturer product page: Click here housing material: 4130 or 4340 Alloy Steel Weight 0.08 lbs	rod end type:	Female Threaded
ball width:0.4370 inthread direction:Right Handlength to ball center:1.3750 ingrade:Precision Extra Capacityoverall height:1.8130 inthread type:UNF-3Bseries:Spherco®lubrication type:Non-Lubricatablemanufacturer product page:Click herehousing material:4130 or 4340 Alloy SteelWeight0.08 lbs	head width:	0.3440 in
thread direction: Right Hand length to ball center: 1.3750 in grade: Precision Extra Capacity overall height: 1.8130 in thread type: UNF-3B series: Spherco® lubrication type: Non-Lubricatable manufacturer product page: Click here housing material: 4130 or 4340 Alloy Steel Weight 0.08 lbs	shank thread size:	5/16-24
length to ball center:1.3750 ingrade:Precision Extra Capacityoverall height:1.8130 inthread type:UNF-3Bseries:Spherco®lubrication type:Non-Lubricatablemanufacturer product page:Click herehousing material:4130 or 4340 Alloy SteelWeight0.08 lbs	ball width:	0.4370 in
grade:Precision Extra Capacityoverall height:1.8130 inthread type:UNF-3Bseries:Spherco®lubrication type:Non-Lubricatablemanufacturer product page:Click herehousing material:4130 or 4340 Alloy SteelWeight0.08 lbs	thread direction:	Right Hand
overall height:1.8130 inthread type:UNF-3Bseries:Spherco®lubrication type:Non-Lubricatablemanufacturer product page:Click herehousing material:4130 or 4340 Alloy SteelWeight0.08 lbs	length to ball center:	1.3750 in
thread type: UNF-3B series: Spherco® lubrication type: Non-Lubricatable manufacturer product page: Click here housing material: 4130 or 4340 Alloy Steel Weight 0.08 lbs	grade:	Precision Extra Capacity
series: Spherco® lubrication type: Non-Lubricatable manufacturer product page: Click here housing material: 4130 or 4340 Alloy Steel Weight 0.08 lbs	overall height:	1.8130 in
lubrication type:Non-Lubricatablemanufacturer product page:Click herehousing material:4130 or 4340 Alloy SteelWeight0.08 lbs	thread type:	UNF-3B
manufacturer product page:Click herehousing material:4130 or 4340 Alloy SteelWeight0.08 lbs	series:	Spherco®
housing material:4130 or 4340 Alloy SteelWeight0.08 lbs	lubrication type:	Non-Lubricatable
Weight 0.08 lbs	manufacturer product page:	Click here
	housing material:	4130 or 4340 Alloy Steel
ball material: 52100 Alloy Steel	Weight	0.08 lbs
	ball material:	52100 Alloy Steel

	7400179748
race material: Alu	uminum Bronze