

# SKF 7000 ACE/P4AH angular contact ball bearings

100% Authentic. SKF 7000 ACE/P4AH angular contact ball bearings Highest 0.0 Inventory REXNORD Manufacturer Name N/A Minimum Buy Quantity Quality. Certified Supplier.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | REXNORD  |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 0.77   |
| EAN                       | 0662327725532  |
| Product Group             | M06110   |
| Number of Mounting Holes  | 3  |
| Mounting Method           | Set Screw  |
| Housing Style             | 3 Bolt Flange Bracket  |
| Rolling Element           | Ball Bearing   |
| Housing Material          | Nickel Coated Cast Iron  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 3/8 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | SG214EL  |
| Seals                     | Single Lip Contact   |
| Housing Configuration     | 1 Piece Solid  |
| Pilot Configuration       | No Pilot   |
| Inch – Metric             | Inch   |
| Long Description          | 3 Bolt Flange Bracket; 7/8" Bore; 1-1/8" Bolt Spacing; 1 Piece Solid; Set Screw Mount; Nic |

|                                    |  |
|------------------------------------|--|
| Other Features                     | Single Row   Spherical   Intermediate Duty   Extended Inner Race |
| UNSPSC                             | 31171501   |
| Harmonized Tariff Code             | 8483.20.40.40  |
| Noun                               | Bearing  |
| Keyword String                     | Flanged  |
| Manufacturer Item Number           | FB3S214EK75  |
| Manufacturer Internal Number       | 5872553  |
| Weight / LBS                       | 1.7  |
| d                                  | 0.875 Inch   22.225 Millimeter                                   |
| Nominal Bolt Circle Diameter Round | 0 Inch   0 Millimeter  |
| Cartridge Pilot Diameter           | 0 Inch   0 Millimeter  |
| Cartridge Pilot Depth              | 0 Inch   0 Millimeter  |
| Bolt Spacing                       | 1.125 Inch   28.58 Millimeter                                    |
| D                                  | 1.172 Inch   29.77 Millimeter                                    |