

# SKF 7019 ACD/HCP4A angular contact ball bearings

Our highly-skilled and factory-trained service experts have the resources to help you with all your SKF 7019 ACD/HCP4A angular contact ball bearings needs – including 0.0 Inventory routine maintenance, major repairs, warranty service, and equipment inspections.

|                           |                          |
|---------------------------|--------------------------|
| Inventory                 | 0.0                      |
| Manufacturer Name         | TIMKEN                   |
| Minimum Buy Quantity      | N/A                      |
| Weight                    | 8.626                    |
| EAN                       | 0883450226929            |
| Product Group             | M06288                   |
| Number of Mounting Holes  | 2                        |
| Mounting Method           | V Lock                   |
| Housing Style             | 2 Bolt Pillow Block      |
| Rolling Element           | Spherical Roller Bearing |
| Housing Material          | Cast Steel               |
| Expansion / Non-expansion | Non-expansion            |
| Mounting Bolts            | 5/8 Inch                 |
| Relubricatable            | Yes                      |
| Insert Part Number        | 22214                    |
| Seals                     | Triple Lip Urethane      |
| Housing Configuration     | 1 Piece Solid            |
| Inch – Metric             | Metric                   |
| Other Features            | Double Row   Single Nut  |

|                               |   |
|-------------------------------|---|
| Long Description              | 2 Bolt Pillow Block; 65MM Bore; 70MM Base to Center Height; V Lock Mount; Spherical Roller Bearing; |
| UNSPSC                        | 31171511  |
| Harmonized Tariff Code        | 8483.20.40.80   |
| Noun                          | Bearing   |
| Keyword String                | Pillow Block  |
| Manufacturer Item Number      | QVP14V065S0   |
| Weight / LBS                  | 19  |
| d                             | 2.559 Inch   65 Millimeter  |
| D                             | 3.19 Inch   81.026 Millimeter   |
| B                             | 2.756 Inch   70 Millimeter  |
| Bolt Spacing Minimum          | 6.875 Inch   174.625Millimeter  |
| Bolt Spacing Maximum          | 8.62 Inch   218.948Millimeter   |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter  |
| Nominal Bolt Center to Center | 7.8 Inch   199.2 Millimeter   |