

SKF 7019 ACE/HCP4AL1 angular contact ball bearings

What are the dimensions of a SKF 7019 ACE/HCP4AL1 angular contact ball bearings? Manufacturing 107.95 mm da Service . Get Your Free, Instant Quote

da	107.95 mm
Da	180 mm
Ca	55.804 mm
A1	111.125 mm
A2	155.575 mm
ba	46.831 mm
H	217.488 mm
H1	114.3 mm
H2	44.45 mm
J min.	295.275 mm
J max.	333.375 mm
L	387.35 mm
N1	25.4 mm
R1	58.737 mm
R2	30.163 mm
RG	3/8 NPT
PG	1/4 NPT
h	39.688 mm
Housing	SAF 024 KA
Bearing	23024 CCK/W33
Adapter sleeve assembly	SNW 3024x4.1/4
Stabilizing ring	2 x 38151-24

Labyrinth ring	2 x LOR 114
PosiTrac Plus contact element	2 x B10724-113
End plug (suffix Y)	EPR 14
Max. speed for PosiTrac Plus seal	1350 r/min
P60°	136 kN
P90°	81.4 kN
P120°	50.7 kN
P150°	46.3 kN
P180°	55.6 kN
Pa	16.7 kN
Mass pillow block	28.6 kg
Cap bolt	2 x 3/4-10 UNC
Cap bolt recommended tightening torque	203.4 N·m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.875 in
Initial grease fill	181.44 g