

SKF 7028 CD/P4A angular contact ball bearings

Welcome to the SKF 7028 CD/P4A angular contact ball bearings 40 Bore Diameter (mm) online 40x78x22 Size (mm) seller.

| | |
|--|---|
| Size (mm) | 40x78x22 |
| Bore Diameter (mm) | 40 |
| Outer Diameter (mm) | 78 |
| Width (mm) | 22 |
| d | 40 mm |
| D | 78 mm |
| T | 22 mm |
| D1 | 42 mm |
| d1 | 78 mm |
| rmin | 1 mm |
| m | 0,484 kg / Weight |
| Ca | 123000 N / Dynamic load rating (axial) |
| C0a | 385000 N / Static load rating (axial) |
| Cua | 39000 N / Fatigue limit load |
| nG | 4850 1/min / Limiting speed |
| nB | 1780 1/min / Reference speed |
| – K89308-TV / Allocated axial cylindrical roller and cage assembly | K89308TV / Allocated axial cylindrical roller and cage assembly |
| Inventory | 0.0 |
| Manufacturer Name | SCHAEFFLER GROUP |
| Minimum Buy Quantity | N/A |

| | |
|-------------------------------------|--|
| Weight / Kilogram | 0.58 |
| EAN | 4012802031225 |
| Product Group | B04144 |
| Rolling Element | Cylindrical Roller Bearing |
| Self Aligning | No |
| Component Description | Roller Assembly plus Raceways |
| Thrust Bearing | Yes |
| Single or Double Direction | Single Direction |
| Banded | No |
| Cage Material | Polyamide |
| Precision Class | ABEC 1 ISO P0 |
| Other Features | Double Row Axial Cylindrical Roller Very High Axial Load |
| Long Description | 40MM Bore 1; 42MM Bore 2; 78MM Outside Diameter; 22MM Height; Cylindrical Roller Bearing; Single Dir |
| Inch – Metric | Metric |
| UNSPSC | 31171507 |
| Harmonized Tariff Code | 8482.50.00.00 |
| Noun | Bearing |
| Keyword 3 | Cylindrical |
| Keyword String | Thrust Roller Cylindrical |
| Manufacturer Item Number | 89308TN |
| Weight / LBS | 1.067 |
| Bore 1 | 1.575 Inch 40 Millimeter |
| Overall Height with Aligning Washer | 0 Inch 0 Millimeter |
| Outside Diameter | 3.071 Inch 78 Millimeter |
| Height | 0.866 Inch 22 Millimeter |

| | |
|--------|----------------------------|
| Bore 2 | 1.654 Inch 42 Millimeter |
|--------|----------------------------|