

SKF 707 CE/P4AH angular contact ball bearings

SKF 707 CE/P4AH angular contact ball bearings, Units and Housings CAD models , Manufacturing Service H 2315 Adapter sleeve . Get C 2315 K Bearing (basic designation) Your Free.

| | |
|-----------------------------|----------------|
| Bearing (basic designation) | C 2315 K |
| Adapter sleeve | H 2315 |
| Locating ring | 2 x FRB 5/160 |
| End cover | ASNH 518-615 R |
| Housing | SNL 518-615 RU |
| Oil seal | 2 x TSN 615 U |
| da | 65 mm |
| Ca | 65 mm |
| Da | 160 mm |
| A1 | 100 mm |
| A2 | 159 mm |
| H | 194 mm |
| H1 | 100 mm |
| H2 | 35 mm |
| J | 290 mm |
| L | 345 mm |
| N | 28 mm |
| N1 | 22 mm |
| J6 | 317 mm |
| J7 | 35 mm |
| N4 max. | 8 mm |
| P0° | 430 kN |

| | |
|---|---------|
| P55° | 550 kN |
| P90° | 340 kN |
| P120° | 250 kN |
| P150° | 215 kN |
| P180° | 275 kN |
| Pa | 180 kN |
| Q120° | 400 kN |
| Q150° | 230 kN |
| Q180° | 200 kN |
| Mass housing | 12.5 kg |
| Cap bolt, size | M 16×90 |
| Cap bolt, rec. tightening torque | 150 N·m |
| Appropriate attachment bolt, size G | 20 mm |
| Appropriate attachment bolt, rec. tightening torque | 385 N·m |
| Oil level, min. | 34 mm |
| Oil level, max. | 41 mm |