

SKF 71964 CDMA/HCP4A angular contact ball bearings

LET OUR SKF 71964 CDMA/HCP4A angular contact ball bearings EXPERTS GET YOU 78x60x10 Size (mm) 78 Bore Diameter (mm) THE PARTS YOU NEED.

Size (mm)	78x60x10
Bore Diameter (mm)	78
Outer Diameter (mm)	60
Width (mm)	10
d	60 mm
D	78 mm
B	10 mm
d1	65.6 mm
D1	72.4 mm
r1,2 – min.	0.3 mm
da – min.	62 mm
Da – max.	76 mm
ra – max.	0.3 mm
Basic dynamic load rating – C	11.9 kN
Basic static load rating – C0	11.4 kN
Fatigue load limit – Pu	0.49 kN
Reference speed	17000 r/min
Limiting speed	11000 r/min
Calculation factor – kr	0.015
Calculation factor – f0	16.9
Inventory	2.0
Manufacturer Name	SKF

Minimum Buy Quantity	N/A
Weight / Kilogram	0.119
EAN	7316576641541
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	60MM Bore; 78MM Outside Diameter; 10MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	61812
Weight / LBS	0.26
Outer Race Width	0.394 Inch 10 Millimeter
Outside Diameter	3.071 Inch 78 Millimeter
Bore	2.362 Inch 60 Millimeter
bore diameter:	60 mm
static load capacity:	11.4 kN
outside diameter:	78 mm
precision rating:	Not Rated

overall width:	10 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Open
outer ring width:	10 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	0.3 mm
snap ring included:	Without Snap Ring
maximum rpm:	11000 RPM
internal clearance:	C0
series:	61
dynamic load capacity:	11.9 kN
d1 ≈	65.4 mm
D1 ≈	72.9 mm
D2 ≈	0 mm
r1,2 min.	0.3 mm
da min.	62 mm
Da max.	76 mm
ra max.	0.3 mm
Basic dynamic load rating C	11.4 kN
Basic static load rating C0	11 kN
Fatigue load limit Pu	0.465 kN
Calculation factor kr	0.015
Calculation factor f0	16.9
Mass bearing	0.11 kg