

# SKF BT1-0056/Q tapered roller bearings

SKF BT1-0056/Q tapered roller bearings Deal is your source for 140 Bore Diameter (mm) OEM 140x80x26 Size (mm) and accessories. We sell Genuine at 80 Outer Diameter (mm) discount prices.

Size (mm)	140x80x26
Bore Diameter (mm)	140
Outer Diameter (mm)	80
Width (mm)	26
d	80 mm
D	140 mm
B	26 mm
d1	103.55 mm
d2	91.44 mm
D1	117.85 mm
a	59 mm
r1,2 – min.	2 mm
r3,4 – min.	1 mm
da – min.	91 mm
Da – max.	130 mm
Db – max.	134 mm
ra – max.	2 mm
rb – max.	1 mm
Basic dynamic load rating – C	85 kN
Basic static load rating – C0	75 kN
Fatigue load limit – Pu	3 kN

Reference speed	5600 r/min
Limiting speed	5600 r/min
Calculation factor – kr	0.095
Calculation factor – ka	1.4
Calculation factor – e	1.14
Calculation factor – X	0.35
Calculation factor – Y0	0.26
Calculation factor – Y1	0.55
Calculation factor – Y2	0.57
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	1.58
EAN	7316577149893
Product Group	B00308
Enclosure	Open
Flush Ground	Yes
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 3   ISO P6
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Brass
Contact Angle	40 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Preload	Light
Mounting Arrangement	Universal
Inch – Metric	Metric

Long Description	80MM Bore; 140MM Outside Diameter; 26MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of B
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer Item Number	7216 BEGAM
Weight / LBS	3.483
Width	1.024 Inch   26 Millimeter
Bore	3.15 Inch   80 Millimeter
Outside Diameter	5.512 Inch   140 Millimeter
d1 ≈	103.55 mm
d2 ≈	91.44 mm
D1 ≈	117.85 mm
r1,2 min.	2 mm
r3,4 min.	1 mm
da min.	91 mm
Da max.	130 mm
Db max.	134 mm
ra max.	2 mm
rb max.	1 mm
Basic dynamic load rating C	85 kN
Basic static load rating C0	75 kN
Fatigue load limit Pu	3.05 kN
Calculation factor A	0.0801
Calculation factor kr	0.095
Calculation factor e	1.14
Calculation factor X	0.57

Calculation factor Y0	0.52
Calculation factor Y2	0.93
Calculation factor Y1	0.55
Mass bearing	1.45 kg