

# SKF BT2B 328957 tapered roller bearings

SKF BT2B 328957 tapered roller bearings with easy-to-use parts graphics, giving you the ability to check parts availability, Mounted Bearing Engineering Group pricing, examine remanufactured options.

|                         |                        |
|-------------------------|------------------------|
| Engineering Group       | Mounted Bearing        |
| Shaft Size              | 6-7/16 in              |
| Shaft Size Type         | Imperial               |
| Full Timken Part Number | QMPX34J607SB           |
| Locking Style           | Eccentric              |
| Weight                  | 395 lb                 |
| Housing Style           | Four-Bolt Pillow Block |
| UPC Code                | 0883450095624          |
| Dimension A             | 7.88 in                |
| Dimension B             | 15.75 in               |
| Dimension C             | 9.25 in                |
| Dimension D Max         | 24.38 in               |
| Dimension D Min         | 21.63 in               |
| Dimension E             | 4.44 in                |
| Dimension F             | 28.00 in               |
| Dimension G             | 7.5000 in              |
| Dimension H             | 2.88 in                |
| Dimension K             | 3.35 in                |
| Dimension L             | 8.83 in                |
| Dimension M             | 5.08 in                |
| Dimension R             | 0.22 in                |

|                                     |           |
|-------------------------------------|-----------|
| Dimension S                         | 8.430 in  |
| C0 – Static Load                    | 494000 lb |
| C – Dynamic Load (Basic)            | 373000 lb |
| e – Geometry Factor                 | 0.33      |
| Y1 – Geometry Factor                | 2.08      |
| Y2 – Geometry Factor                | 3.09      |
| Oil Lubrication – M/N Seal          | 600 rpm   |
| Oil Lubrication – T Seal            | 900 rpm   |
| Oil Lubrication – B/C/O Seal        | 350 rpm   |
| Grease Lubrication – M/N Seal       | 600 rpm   |
| Grease Lubrication – T Seal         | 800 rpm   |
| Grease Lubrication – B/C/O Seal     | 350 rpm   |
| Float                               | 0.083 in  |
| Shaft Tolerance                     | 0.0050 in |
| Eng Internal Radial Clearance – Min | 0.0047    |
| Eng Internal Radial Clearance – Max | 0.0071    |
| Pre Install Clearance Min           | 0.0047 in |
| Pre Install Clearance Max           | 0.0071 in |