

SKF BT2B 332823/HA1 tapered roller bearings

170 Million used SKF BT2B 332823/HA1 tapered roller bearings instantly searchable. Shop our large selection of 110x150x20 Size (mm) parts based on brand, price, description, and 110 Bore Diameter (mm) location. Order the 150 Outer Diameter (mm) with stock ...

Size (mm)	110x150x20
Bore Diameter (mm)	110
Outer Diameter (mm)	150
Width (mm)	20
d	110 mm
D	150 mm
B	20 mm
C	20 mm
Angle (α)	25 °
a	47,5 mm
r min.	1,1 mm
r1 min.	0,6 mm
da min.	117 mm
db min	117 mm
ra max.	1 mm
Weight	1,01 Kg
Basic dynamic load rating (C)	49,5 kN
Basic static load rating (C0)	56 kN
(Grease) Lubrication Speed	4 200 r/min
Contact angle α	30 °

rs min	1.1 mm
r1s min	0.6 mm
Mass	1.01 kg
Dynamic load, C	49.5 kN
Static load, C0	56 kN
Fatigue limit load, Cu	2.23 kN
Nlim (oil)	5,700 rpm
Nlim (grease)	4,200 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
da min	117 mm
Da max	143 mm
Db max	145.5 mm
r1a max	0.6 mm
ra max	1 mm