

SKF C 3022 K + AHX 3122 cylindrical roller bearings

Our highly-skilled and factory-trained service experts have the resources to help you with all your SKF C 3022 K + AHX 3122 cylindrical roller bearings needs – including routine maintenance, major repairs, warranty 95.0 Inventory service, and equipment inspections.

| | |
|---------------------------|---------------------|
| Inventory | 95.0 |
| Manufacturer Name | EBC |
| Minimum Buy Quantity | N/A |
| Weight | 2.295 |
| Product Group | M06110 |
| Number of Mounting Holes | 2 |
| Mounting Method | Set Screw |
| Housing Style | 2 Bolt Flange Block |
| Rolling Element | Ball Bearing |
| Housing Material | Cast Iron |
| Expansion / Non-expansion | Non-expansion |
| Mounting Bolts | 1/2 Inch |
| Relubricatable | Yes |
| Insert Part Number | UC210-30 |
| Seals | B Seal |
| Housing Configuration | 1 Piece Solid |
| Pilot Configuration | No Pilot |
| Inch – Metric | Inch |

| | |
|------------------------------------|---|
| Long Description | 2 Bolt Flange Block; 1-7/8" Bore; 6.2" Bolt Circle; 6-3/16" Bolt Spacing; 1 Piece Sol |
| Other Features | Single Row Spherical Gray Epoxy Paint Finish |
| UNSPSC | 31171501 |
| Harmonized Tariff Code | 8483.20.40.40 |
| Noun | Bearing |
| Keyword String | Flanged |
| Manufacturer Item Number | UCFL 210 |
| Weight / LBS | 5.06 |
| d | 1.875 Inch 47.625 Millimeter |
| Nominal Bolt Circle Diameter Round | 6.2 Inch 157 Millimeter |
| Cartridge Pilot Depth | 0 Inch 0 Millimeter |
| Bolt Spacing | 6.188 Inch 157.175 Millimeter |
| Cartridge Pilot Diameter | 0 Inch 0 Millimeter |
| D | 2.014 Inch 51.156 Millimeter |