## SKF C 3044 cylindrical roller bearings

SKF C 3044 cylindrical roller bearings Warehouse offers car parts and car accessories. We sell discount TIMKEN Manufacturer Name online as 0.0 Inventory well as cheap machinery parts.

| Inventory                 | 0.0                       |
|---------------------------|---------------------------|
| Manufacturer Name         | TIMKEN                    |
| Minimum Buy Quantity      | N/A                       |
| Weight                    | 4.994                     |
| EAN                       | 0883450155045             |
| Product Group             | M06288                    |
| Number of Mounting Holes  | 2                         |
| Mounting Method           | Eccentric Collar          |
| Housing Style             | 2 Bolt Pillow Block       |
| Rolling Element           | Spherical Roller Bearing  |
| Housing Material          | Cast Steel                |
| Expansion / Non-expansion | Non-expansion             |
| Mounting Bolts            | 5/8 Inch                  |
| Relubricatable            | Yes                       |
| Insert Part Number        | 22210                     |
| Seals                     | Triple Lip Nitrile Rubber |
| Housing Configuration     | 1 Piece Solid             |
| Inch — Metric             | Metric                    |
| Other Features            | Double Row                |

| Long Description                 | 2 Bolt Pillow Block; 50MM Bore;<br>57.2MM Base to Center Height;<br>Eccentric Collar Mount;<br>Spherical Roll |
|----------------------------------|---|
| UNSPSC                           | 31171511  |
| Harmonized Tariff Code           | 8483.20.40.80   |
| Noun                             | Bearing   |
| Keyword String                   | Pillow Block  |
| Manufacturer Item Number         | QMPL10J050SM  |
| Weight / LBS                     | 13  |
| d                                | 1.969 Inch   50 Millimeter  |
| Nominal Bolt Center to<br>Center | 6.1 Inch   156 Millimeter   |
| Bolt Spacing Maximum             | 6.36 Inch   161.544Millimeter   |
| Actual Bolt Center to Center     | 0 Inch   OMillimeter  |
| D                                | 2.87 Inch   72.898 Millimeter   |
| Bolt Spacing Minimum             | 5.93 Inch   150.622Millimeter   |
| В                                | 2.252 Inch   57.2 Millimeter  |