## SKF C 3168 KM + OH 3168 H cylindrical roller bearings

Shop SKF C 3168 KM + OH 3168 H cylindrical roller bearings N/A Minimum Buy Quantity huge online discount inventory. and Import machinery parts 0.0 Inventory your car needs with Free Shipping and Free Extended Warranty.

| Inventory                 | 0.0  |
|---------------------------|--|
| Manufacturer Name         | REXNORD                                    |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 133.476                                    |
| EAN                       | 0698210002473                              |
| Product Group             | M06288                                     |
| Number of Mounting Holes  | 4  |
| Mounting Method           | Tapered Adapter Sleeve                     |
| Housing Style             | 4 Bolt Pillow Block                        |
| Rolling Element           | Spherical Roller Bearing                   |
| Housing Material          | Cast Iron                                  |
| Expansion / Non-expansion | Non-expansion                              |
| Mounting Bolts            | 1-1/8 Inch                                 |
| Relubricatable            | Yes  |
| Insert Part Number        | 9507U                                      |
| Seals                     | Heavy Contact                              |
| Housing Configuration     | 1 Piece Solid                              |
| Inch — Metric             | Inch                                       |
| Other Features            | Double Row   Two Open Auxiliary<br>End Cap |

| Long Description              | 4 Bolt Pillow Block; 5-7/16"<br>Bore; 7-1/16" Base to Center<br>Height; Tapered Adapter Sleeve<br>M |
|-------------------------------|---|
| UNSPSC                        | 31171511  |
| Harmonized Tariff Code        | 8483.20.40.80   |
| Noun                          | Bearing   |
| Keyword String                | Pillow Block  |
| Manufacturer Item Number      | AMP9507F  |
| Manufacturer Internal Number  | 6800247   |
| Weight / LBS                  | 250   |
| Bolt Spacing Maximum          | 0 Inch   OMillimeter  |
| D                             | 11.063 Inch   281 Millimeter  |
| d                             | 5.438 Inch   138.125 Millimeter   |
| В                             | 7.063 Inch   179.4 Millimeter   |
| Nominal Bolt Center to Center | 20.5 Inch   520.7 Millimeter  |
| Actual Bolt Center to Center  | 20.5 Inch   520.7Millimeter   |
| Bolt Spacing Minimum          | 0 Inch   OMillimeter  |