

SKF C 3232 cylindrical roller bearings

Manufacturers of all are represented in our partial list of clients. Contact 65 mm d 120 mm D Gary for 31 mm B a complete SKF C 3232 cylindrical roller bearings list of clients and projects.

| | |
|---------------------------------|-----------|
| d | 65 mm |
| D | 120 mm |
| B | 31 mm |
| C | 27 mm |
| T | 32.75 mm |
| d1 | 91.1 mm |
| a | 27.4 mm |
| rs min | 2 mm |
| r1s min | 1.5 mm |
| e | 0.4 |
| Y2 | 1.48 |
| Y0 | 0.81 |
| Mass | 1.56 kg |
| ISO 355 reference | T3EC065 |
| Dynamic load, C | 169 kN |
| Rating life coefficient, A2 | 1 |
| Static load, C0 | 222 kN |
| Fatigue limit load, Cu | 27.1 kN |
| Nref | 3,500 rpm |
| Nlim | 5,900 rpm |
| Min operating temperature, Tmin | -40 °C |

| | |
|---|----------|
| Max operating temperature, Tmax | 120 °C |
| Characteristic cage frequency, FTF | 0.43 Hz |
| Characteristic rolling element frequency, BSF | 6.34 Hz |
| Characteristic outer ring frequency, BPF0 | 8.09 Hz |
| Characteristic inner ring frequency, BRFI | 10.91 Hz |
| da max | 75 mm |
| db min | 75 mm |
| Da min | 104 mm |
| Da max | 111.5 mm |
| Db min | 115 mm |
| Ca min | 4 mm |
| Cb min | 5.5 mm |
| ra max | 2 mm |
| r1a max | 1.5 mm |