## SKF C 4912 V cylindrical roller bearings

170 0.0 Inventory Million used SKF C 4912 V cylindrical roller bearings instantly searchable. Shop our large selection of parts based on brand, price, description, and location. Order the NACHI Manufacturer Name with stock ...

| Inventory                 | 0.0  |
|---------------------------|--|
| Manufacturer Name         | NACHI  |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 0.360 kg   |
| EAN                       | 4991893402827  |
| Product Group             | B04144   |
| Bore Profile              | Straight   |
| Cage Material             | Steel  |
| Precision Class           | RBEC 1   ISO PO  |
| Number of Rows of Rollers | Single Row   |
| Separable                 | Outer Ring — Both Sides  |
| Rolling Element           | Cylindrical Roller Bearing                                     |
| Profile                   | Complete with Outer and Inner<br>Ring                          |
| Snap Ring                 | No   |
| Internal Clearance        | C0-Medium  |
| Retainer                  | Yes  |
| Relubricatable            | Yes  |
| Inch — Metric             | Metric   |
| Other Features            | 2 Rib Inner Ring   Plain Outer<br>Ring   Cage on Inner Ring OD |

| Long Description             | 40MM Bore; Straight Bore<br>Profile; 80MM Outside Diameter;<br>18MM Width; Steel Cage<br>Matetrial; RBEC 1 |
|------------------------------|--|
| UNSPSC                       | 31171547   |
| Harmonized Tariff Code       | 8482.50.00.00  |
| Noun                         | Bearing  |
| Manufacturer Item Number     | N208   |
| Weight / LBS                 | 0.79   |
| d                            | 1.575 Inch   40 Millimeter   |
| D                            | 3.15 Inch   80 Millimeter  |
| В                            | 0.709 Inch   18 Millimeter   |
| Enclosure                    | 0pen   |
| Bore Type                    | Cylindrical Bore   |
| Configuration                | Single Row   |
| Bore Size                    | 40 mm  |
| Outside Ring Inside Diameter | 70 mm  |
| Fillet Radius/Chamfer        | 1.1 mm   |
| r1                           | 1.1 mm   |
| Dynamic Load Rating          | 43,500 N   |
| Static Load Rating           | 43,000 N   |
| Limiting Speed — Grease      | 8,500 rpm  |
| Limiting Speed — Oil         | 10,000 rpm   |
| Radial Clearance             | 0.025 to 0.050 mm  |
| da (min)                     | 47 mm  |
| db (min)                     | 47 mm  |
| db (max)                     | 49 mm  |
| dc (min)                     | 52 mm  |
| Da (max)                     | 73 mm  |
| Db (min)                     | 73 mm  |

| Db (max)  | 72 mm |
|-----------|-------|
| ra (max)  | 1 mm  |
| ral (max) | 1 mm  |