

# SKF C2222K cylindrical roller bearings

How do TIMKEN Manufacturer Name you find the SKF C2222K cylindrical roller bearings specification? Manufacturers Online 0.0 Inventory Free check

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | TIMKEN  |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 12.712  |
| EAN                       | 0883450994248   |
| Product Group             | M06288  |
| Number of Mounting Holes  | 4   |
| Mounting Method           | Concentric Collar   |
| Housing Style             | 4 Bolt Round Flange Block   |
| Rolling Element           | Spherical Roller Bearing  |
| Housing Material          | Cast Steel  |
| Expansion / Non-expansion | Non-expansion   |
| Mounting Bolts            | 3/4 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | 22215   |
| Seals                     | Triple Lip Urethane   |
| Housing Configuration     | 1 Piece Solid   |
| Pilot Configuration       | With Pilot  |
| Inch – Metric             | Inch  |
| Long Description          | 4 Bolt Round Flange Block;<br>2-3/4" Bore; 7.9" Bolt Circle;<br>5.57" Bolt Spacing; 1 Piece |

|                                    |   |
|------------------------------------|---|
| Other Features                     | Double Row   Single Collar   With Set Screw |
| UNSPSC                             | 31171501                                    |
| Harmonized Tariff Code             | 8483.20.40.80                               |
| Noun                               | Bearing                                     |
| Keyword String                     | Flanged                                     |
| Manufacturer Item Number           | QAFYP15A212S0                               |
| Weight / LBS                       | 28  |
| Bolt Spacing                       | 5.57 Inch   141.478 Millimeter              |
| Cartridge Pilot Diameter           | 6.313 Inch   160.35 Millimeter              |
| d                                  | 2.75 Inch   69.85 Millimeter                |
| Nominal Bolt Circle Diameter Round | 7.9 Inch   200 Millimeter                   |
| D                                  | 3.62 Inch   91.948 Millimeter               |
| Cartridge Pilot Depth              | 0.188 Inch   4.775 Millimeter               |