

SKF C3072KM cylindrical roller bearings

170 Million used SKF C3072KM cylindrical roller bearings instantly searchable. Shop our large selection 70 mm d of parts based on brand, price, description, 70 Bore Diameter (mm) and location. Order 140 mm L4 the with stock ...

| | |
|--------------------|---------|
| Bore Diameter (mm) | 70 |
| d | 70 mm |
| L4 | 140 mm |
| L5 | 36 mm |
| L2 | 27 mm |
| L3 | 155 mm |
| s | 34,2 mm |
| A | 90 mm |
| A1 | 52 mm |
| B1 | 92,1 mm |
| D2 | 102 mm |
| H | 202 mm |
| H1 | 130 mm |
| L | 252 mm |
| L1 | 85 mm |
| N | 46 mm |
| N1 | 85 mm |
| Thread (G) | M10x1 |
| J1 | 26 mm |
| J2 | 180 mm |
| Weight | 11,7 Kg |

| | |
|---|-----------|
| Basic dynamic load rating (C) | 104,26 kN |
| A2 | 52 mm |
| B | 68.3 mm |
| A5 | 34.1 mm |
| d1 | 102 mm |
| G | M10x1 |
| H2 | 130 mm |
| N2 | 85 mm |
| s1 | 64.35 mm |
| S | 34.2 mm |
| SW | 6 mm |
| C | 104.26 kN |
| C0 | 68 kN |
| T min. | -20 °C |
| T max. | 100 °C |
| Recommended tightening torque for set screw | 33 Nm |
| Designation of housing | T314- |
| Designation of bearing | EX314G2 |