

# SKF C4020V cylindrical roller bearings

Browse SKF C4020V cylindrical roller bearings Categories in the Manufacturers Online Free. Composite for food and beverage Housing material including .

| Housing material            | Composite for food and beverage |
|-----------------------------|---------------------------------|
| d                           | 23.812 mm                       |
| A                           | 32 mm                           |
| A1                          | 22 mm                           |
| A5                          | 26.3 mm                         |
| B                           | 34.1 mm                         |
| B4                          | 5 mm                            |
| H                           | 70.5 mm                         |
| H1                          | 36.5 mm                         |
| H2                          | 16 mm                           |
| J                           | 105 mm                          |
| J max.                      | 110 mm                          |
| J min.                      | 100 mm                          |
| L                           | 134 mm                          |
| N                           | 17.5 mm                         |
| N1                          | 12.5 mm                         |
| s1                          | 19.8 mm                         |
| Basic dynamic load rating C | 14 kN                           |
| Basic static load rating C0 | 7.8 kN                          |
| Fatigue load limit Pu       | 0.335 kN                        |
| Limiting speed              | 7000 r/min                      |

|   |                       |
|---|-----------------------|
| Mass bearing unit                                 | 0.34 kg               |
| Thread grub screw G2                              | 1/4-28 UNF            |
| Hexagonal key size for grub screw N               | 3.175 mm              |
| Recommended tightening torque for grub screw      | 4 N·m                 |
| Recommended diameter for attachment bolts, mm G   | 10 mm                 |
| Recommended diameter for attachment bolts, inch G | 0.375 in              |
| Housing   | SYWK 505 Y            |
| Bearing   | YAR 205-015-2RF/VE495 |
| End cover   | ECW 205               |