

# SKF EE843220/290 tapered roller bearings

Advance SKF EE843220/290 tapered roller bearings is 75 Bore Diameter (mm) your source for quality and accessories. shop online for home delivery or pick 75x105x16 Size (mm) up in one of 105 Outer Diameter (mm) our 10000 .

Size (mm)	75x105x16
Bore Diameter (mm)	75
Outer Diameter (mm)	105
Width (mm)	16
d	75 mm
D	105 mm
B	16 mm
C	16 mm
r min.	1 mm
da min.	80 mm
da max	82 mm
Da max.	100 mm
ra max.	1 mm
Weight	0,364 Kg
Basic dynamic load rating (C)	24,4 kN
Basic static load rating (C0)	22,6 kN
(Grease) Lubrication Speed	6 000 r/min
(Oil) Lubrication Speed	7 100 r/min
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A

Weight / Kilogram	0.36
EAN	0029176030116
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	75MM Bore; 105MM Outside Diameter; 16MM Outer Race Diameter; Open; Ball Bearing; ABEC 1   ISO P0; No
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6915
Weight / LBS	0.36
Bore	2.953 Inch   75 Millimeter
Outside Diameter	4.134 Inch   105 Millimeter
Outer Race Width	0.63 Inch   16 Millimeter
bore diameter:	75 mm
internal clearance:	C0
outside diameter:	105 mm
dynamic load capacity:	24400 N
overall width:	16 mm

precision rating:	ABEC1, P0
bore type:	Round
finish/coating:	Uncoated
closure type:	Open
cage material:	Steel Cage
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm:	7100 rpm
snap ring included:	Without Snap Ring
SRI	4.52
hidYobi	6915
LangID	1
D_	105
SREX	0.02
B_	16
da min	80
hidTable	ecat_NSRDGB
Oil rpm	7100
SRE	4.52
mass	0.364
GRS rpm	6000
ra	1
SRIX	0.02
D_a	100
SRIN	-0.02
C0	22.6
fo	16.5
SREN	0
DE_	98.731
Prod_Type3	DGBB_SR_OT

DA_	8.731
bomp	0
Z_	18
yobi	6915
C_conv	24400
ALPHA_	0
SDM_	90
r	1
KBRG	6101
SBRG	19
DI_	81.269