

# SKF FBSA 205/DF thrust ball bearings

SKF FBSA 205/DF thrust ball bearings N/A Minimum Buy Quantity Product Brochures 0.0 Inventory , Manufacturing Service . Get Your Free.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 10.896   |
| EAN                       | 0883450076500  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | V Lock   |
| Housing Style             | 4 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Expansion  |
| Mounting Bolts            | 3/4 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 22215  |
| Seals                     | Triple Lip Nitrile Rubber  |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Inch   |
| Other Features            | Double Row   Double Nut  |
| Long Description          | 4 Bolt Pillow Block; 2-7/16" Bore; 3-1/2" Base to Center Height; V Lock Mount; Spherical R |

|                               |                                |
|-------------------------------|--------------------------------|
| UNSPSC                        | 31171511                       |
| Harmonized Tariff Code        | 8483.20.40.80                  |
| Noun                          | Bearing                        |
| Keyword String                | Pillow Block                   |
| Manufacturer Item Number      | QVVPK15V207SEM                 |
| Weight / LBS                  | 29                             |
| D                             | 4.09 Inch   103.886 Millimeter |
| Nominal Bolt Center to Center | 9.8 Inch   248.9 Millimeter    |
| B                             | 3.5 Inch   88.9 Millimeter     |
| Bolt Spacing Minimum          | 9.06 Inch   230.124Millimeter  |
| Bolt Spacing Maximum          | 10.44 Inch   265.176Millimeter |
| d                             | 2.438 Inch   61.925 Millimeter |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter           |