

# SKF FY 25 FM bearing units

With over 10170 full-service stores, our SKF FY 25 FM bearing units inventory is extensive and our 9 Days or more Days to Ship parts are priced right. within 24 hours. This helps you maximize your productivity by saving time and your hard-earned dollars. Double Shielded Bearing Style

|  |                 |
|--|-----------------|
| Days to Ship   | 9 Days or more  |
| RoHS   | 6               |
| Bearing Style  | Double Shielded |
| d  | 75              |
| D  | 105             |
| B  | 16              |
| Basic Dynamic Load Rating Cr(N)                        | 20800           |
| Allowable Rotational Velocity(Grease Lubrication)(rpm) | 6200            |
| Basic Static Load Rating Cor(N)                        | 19700           |
| Sealing Structure                                      | Double Shielded |
| Type   | Ball            |
| Bearing Ring Material                                  | Steel           |
| Outer Ring Shape                                       | Flat            |
| Precision  | Grade 0         |
| Specifications, Environment                            | Standard        |
| Load Type  | Radial          |
| Number of Raceway Ring Rows                            | Single Row      |
| Size Standards   | Metric System   |
| Transmitter Material                                   | Steel           |
| Retainer Type  | Punching        |
| Inner/Outer Ring Material                              | [Steel] Steel   |

|                                     |                 |
|-------------------------------------|-----------------|
| I.D.(Ø)                             | 75              |
| O.D.(Ø)                             | 105             |
| Width(mm)                           | 16              |
| Basic Dynamic Load Rating(N)        | 24400           |
| Max. Allowed rpm(rpm)               | 6000            |
| Rolling Element Material            | [Steel] Steel   |
| Basic Load Rating, Static Rating(N) | 22600           |
| Clearance sign                      | CN (standard)   |
| Accuracy(Class)                     | Class 0         |
| Acoustic Symbol                     | No              |
| Holder Symbol                       | No              |
| Symbol of Bearing Ring Shape        | No              |
| Seal, Shield Symbols                | ZZ              |
| Precision Grade Symbol              | No              |
| Special Configurations Code         | No              |
| Rubugado Symbol                     | No              |
| Material Symbol                     | No              |
| Spacer, Sleeve symbol               | No              |
| Types                               | No              |
| Load Direction                      | Radial          |
| Outer Ring                          | With Outer Ring |
| Combination symbol                  | No              |
| Low Torque Specification            | No              |
| Internal Symbol                     | No              |
| Torque Symbol                       | No              |
| Specifications/Environment          | Standard        |