

SKF FYR 3 7/16 bearing units

What is SKF FYR 3 7/16 bearing units in mechanical engineering? Manufacturing Service . Upload your CAD file for an instant. 60.325 mm da

| | |
|-------------------------|---------------|
| da | 60.325 mm |
| Da | 160 mm |
| Ca | 64.795 mm |
| A1 | 98.425 mm |
| A2 | 223.838 mm |
| S | 4.763 mm |
| ba | 44.45 mm |
| H | 192.088 mm |
| H1 | 101.6 mm |
| H2 | 41.275 mm |
| J min. | 263.525 mm |
| J max. | 295.275 mm |
| J1 | 53.975 mm |
| L | 349.25 mm |
| N1 | 19.05 mm |
| R1 | 60.325 mm |
| R2 | 27.94 mm |
| RG | 3/8 NPT |
| PG | 1/8 NPT |
| h | 40.481 mm |
| Housing | FSAF 615 |
| Bearing | 22315 EK |
| Adapter sleeve assembly | SNW 115×2.3/8 |

| | |
|--|----------------|
| Stabilizing ring | SR-18-15 |
| Taconite seal | TER 36 |
| End plug (suffix Y) | EPR 7 |
| Max. speed for Taconite seal | 1250 r/min |
| P60° | 101 kN |
| P90° | 60.9 kN |
| P120° | 38.3 kN |
| P150° | 34.7 kN |
| P180° | 42.3 kN |
| Pa | 12.5 kN |
| Mass pillow block | 23.6 kg |
| Cap bolt | 2 x 5/8-11 UNC |
| Cap bolt recommended tightening torque | 298.3 N·m |
| Cap bolt, SAE grade | 8 |
| Appropriate attachment bolt size G | 0.625 in |
| Initial grease fill | 141.75 g |