

# SKF FYTB 30 TF bearing units

SKF FYTB 30 TF bearing units Needs Analysis , IPTCI BEARINGS  
Manufacturer Name 0.0 Inventory N/A Minimum Buy Quantity  
Manufacturing Service . Get Your Free.

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | IPTCI BEARINGS  |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 1.542   |
| Product Group             | M06110  |
| Number of Mounting Holes  | 2   |
| Mounting Method           | Set Screw   |
| Housing Style             | 2 Bolt Flange Block   |
| Rolling Element           | Ball Bearing  |
| Housing Material          | Cast Iron   |
| Expansion / Non-expansion | Non-expansion   |
| Mounting Bolts            | 7/16 Inch   |
| Relubricatable            | Yes   |
| Insert Part Number        | SB208-24G   |
| Seals                     | K Seal  |
| Housing Configuration     | 1 Piece Solid   |
| Pilot Configuration       | No Pilot  |
| Inch – Metric             | Inch  |
| Long Description          | 2 Bolt Flange Block; 1-1/2" Bore; 5.7" Bolt Circle; 5-21/32" Bolt Spacing; 1 Piece So |
| Other Features            | Single Row   Narrow Inner Race  |

|                                       |                                   |
|---------------------------------------|-----------------------------------|
| UNSPSC                                | 31171501                          |
| Harmonized Tariff Code                | 8483.20.40.40                     |
| Noun                                  | Bearing                           |
| Keyword String                        | Flanged                           |
| Manufacturer Item Number              | SBFL 208 24 G                     |
| Weight / LBS                          | 3.4                               |
| Cartridge Pilot Diameter              | 0 Inch   0 Millimeter             |
| d                                     | 1.5 Inch   38.1 Millimeter        |
| D                                     | 1.417 Inch   36 Millimeter        |
| Nominal Bolt Circle Diameter<br>Round | 5.7 Inch   144 Millimeter         |
| Bolt Spacing                          | 5.656 Inch   143.67<br>Millimeter |
| Cartridge Pilot Depth                 | 0 Inch   0 Millimeter             |