

SKF GE240TXA-2LS plain bearings

SKF GE240TXA-2LS plain bearings SEARCH – Whether it's agriculture or construction equipment your working on, Has the you need.

Size (mm)	107.95×159.987×34.925
Bore Diameter (mm)	107,95
Outer Diameter (mm)	159,987
Width (mm)	34,925
d	107,95 mm
D	159,987 mm
T	34,925 mm
B	34,925 mm
C	26,988 mm
ra1 max.	3,3 mm
a	33,7 mm
r min.	3,5 mm
r1 min.	3,3 mm
Da	146 mm
db	116 mm
ra max.	3,5 mm
da	122 mm
Db	154 mm
Weight	2,434 Kg
Basic dynamic load rating (C)	164 kN
Basic static load rating (C0)	315 kN

(Grease) Lubrication Speed	2000 r/min
(Oil) Lubrication Speed	2800 r/min
Calculation factor (e)	0,4
Calculation factor (Y0)	0,82
LangID	1
ALP23	0
outer r	3.3
ALP22	0
D_	159.987
ALP21	30
SHOG_yobi	LM522546R/LM522510R
RAr	292.143
inner r	3.5
GRS rpm	2000
D_b	154
D_a	146
DE_	144.224
SLR	25.3
Prod_Type3	TRBSR_ID_A
BETA_	1
ALPHA_	15
SDM_	135.231
DA1	10.197
DA2	9.316
hidYobi	LM522546/LM522510
Y1	1.5
B_	34.925
Oil rpm	2800
hidTable	ecat_NSTPRI

Y0	0.82
inner ra	3.5
outer rb	3.3
C0	315
CUP	0.784
e	0.4
DA_	9.757
BET21	2
BET22	0
BET23	0
Z_	34
C_	26.988
yobi	LM522546/LM522510
KBRG	3161
CONE	1.65
DI_	125.679