

SKF GEG 20 ES plain bearings

Advance SKF GEG 20 ES plain bearings is your source for quality and accessories. shop online 40 mm da 65 mm B for home delivery or pick up in one of our 10000 .

| | |
|-----------------------------|------------|
| da | 40 mm |
| A | 60 mm |
| B | 65 mm |
| H | 114 mm |
| H1 | 60 mm |
| H2 | 25 mm |
| J | 170 mm |
| L | 205 mm |
| N | 20 mm |
| N1 | 15 mm |
| A3 | 51 mm |
| A5 | 23.5 mm |
| ba min. | 34 mm |
| ba max. | 43 mm |
| J6 | 185 mm |
| J7 | 21 mm |
| N4 max. | 6 mm |
| Basic dynamic load rating C | 96.5 kN |
| Basic static load rating C0 | 90 kN |
| Fatigue load limit Pu | 9.8 kN |
| Limiting speed | 1900 r/min |
| Calculation factor e | 0.28 |
| Calculation factor Y1 | 2.4 |

| | |
|--|---------|
| Calculation factor Y2 | 3.6 |
| Bearing mean diameter dm | 60 mm |
| Basic bearing designation | 22208 E |
| P0° | 160 kN |
| P55° | 265 kN |
| P90° | 160 kN |
| P120° | 100 kN |
| P150° | 90 kN |
| P180° | 110 kN |
| Pa | 15 kN |
| Mass bearing unit | 3.8 kg |
| Attachment bolt diameter G | 12 mm |
| Tightening torque for attachment bolts | 80 N·m |
| Grub screws | 3 x M 6 |
| Tightening torque for grub screws | 8 N·m |
| Grease quantity for relubrication | 4 g |
| End cover | ECY 208 |