

SKF GEZ600ES-2RS plain bearings

How do I place an EMERGENCY order for a SKF GEZ600ES-2RS plain bearings that I want to pick up at 25x47x12 Size (mm) at our store?

| | |
|---|-----------|
| Size (mm) | 25x47x12 |
| Bore Diameter (mm) | 25,000 |
| Outer Diameter (mm) | 47,000 |
| Width (mm) | 12,000 |
| d | 25,000 mm |
| D | 47,000 mm |
| B | 12,000 mm |
| C | 12,000 mm |
| d1 | 30.2 mm |
| D1 | 42 mm |
| rs min | 0.6 mm |
| Radial clearance class | CN |
| Mass | 0.08 kg |
| Dynamic load, C | 9.8 kN |
| Static load, C0 | 5.9 kN |
| Fatigue limit load, Cu | 0.34 kN |
| f0 | 14.5 |
| Nlim | 9,500 rpm |
| Min operating temperature, Tmin | -20 °C |
| Max operating temperature, Tmax | 120 °C |
| Characteristic cage frequency, FTF | 0.41 Hz |
| Characteristic rolling element frequency, BSF | 5.49 Hz |

| | |
|---|---------|
| Characteristic outer ring frequency, BPF0 | 4.12 Hz |
| Characteristic inner ring frequency, BPF1 | 5.88 Hz |
| da min | 29 mm |
| da max | 30.2 mm |
| Da max | 43 mm |
| ra max | 0.6 mm |