

SKF GEZM308ES-2RS plain bearings

High Quality SKF GEZM308ES-2RS plain bearings. Competitive Pricing. Accept Small 34 Outer Diameter (mm) Order. Easy and Fast 23.812x34x13.5 Size (mm) Shipping.

| | |
|---------------------|----------------|
| Size (mm) | 23.812x34x13.5 |
| Bore Diameter (mm) | 23,812 |
| Outer Diameter (mm) | 34 |
| Width (mm) | 13,5 |
| d | 23.812 mm |
| A | 34 mm |
| A1 | 13.5 mm |
| A2 | 25 mm |
| A5 | 18 mm |
| B | 34.1 mm |
| H | 19 mm |
| H1 | 76 mm |
| H2 | 53 mm |
| L | 100 mm |
| L1 | 64 mm |
| L2 | 10 mm |
| L3 | 52 mm |
| N1 | 16 mm |
| N2 | 33 mm |
| s1 | 19.8 mm |
| DN | 6.5 mm |
| SWN | 7 mm |

| | |
|--|----------------|
| GN – 1/4-28 SAE-LT | 1/428 SAELT |
| RG – 1/4-28 UNF | 1/428 UNF |
| R1 | 2 mm |
| R α | 30 ° |
| Basic dynamic load rating – C | 14 kN |
| Basic static load rating – C0 | 7.8 kN |
| Fatigue load limit – Pu | 0.335 kN |
| Limiting speed with shaft tolerance h6 | 7000 r/min |
| Mass bearing unit | 0.88 kg |
| Grub (set) screw – G2 – 1/4-28 UNF | 1/428 UNF |
| Hexagonal key size for grub screw – H | 3.175 mm |
| Recommended tightening torque for grub screw | 4 N·m |
| Housing material | Cast iron |
| B4 | 5 mm |
| N | 19 mm |
| RG | 1/4-28 UNF |
| R α | 30 ° |
| GN | 1/4-28 SAE-LT |
| Basic dynamic load rating C | 14 kN |
| Basic static load rating C0 | 7.8 kN |
| Fatigue load limit Pu | 0.335 kN |
| Grub (set) screw G2 | 1/4-28 UNF |
| Hexagonal key size for grub screw N | 3.175 mm |
| Housing | TU 505 M |
| Bearing | YAR 205-015-2F |
| End cover | ECY 205 |