

SKF GX 25 F plain bearings

SKF GX 25 F plain bearings Industries and Applications Imperial Design Units ? We sell discount online as well as cheap 25878 Cone Part Number machinery parts.

| | |
|---|---------------|
| Cone Part Number | 25878 |
| Design Units | Imperial |
| Cage Type | Stamped Steel |
| C1 – Dynamic Radial Rating (Two-Row, 1 million revolutions) ¹ | 33300 lbf |
| C90(2) – Dynamic Radial Rating (Two-Row, 90 million revolutions) ² | 8640 lbf |
| d | 1.3750 in |
| B – Cone Width | 0.9688 in |
| R – Cone Backface To Clear Radius ³ | 0.14 in |
| da – Cone Frontface Backing Diameter | 1.59 in |
| db – Cone Backface Backing Diameter | 1.85 in |
| Ab – Cage-Cone Frontface Clearance | 0.09 in |
| Aa – Cage-Cone Backface Clearance | 0.02 in |
| a – Effective Center Location ⁴ | -0.32 in |
| C90 – Dynamic Radial Rating (90 million revolutions) ⁵ | 4960 lbf |
| C1 – Dynamic Radial Rating (1 million revolutions) ⁶ | 19100 lbf |
| C0 – Static Radial Rating | 21900 lbf |
| Ca90 – Dynamic Thrust Rating (90 million revolutions) ⁷ | 2460 lbf |
| K – Factor ⁸ | 2.01 |
| G1 – Heat Generation Factor (Roller-Raceway) | 26.4 |

| | |
|--|--------|
| G2 – Heat Generation Factor (Rib-Roller End) | 10.9 |
| Cg – Geometry Factor | 0.0695 |