

SKF LM 742747/710 tapered roller bearings

SKF LM 742747/710 tapered roller bearings Warehouse offers car parts and car accessories. We sell discount online as well 30 mm d as cheap machinery parts.

d	30 mm
D	62 mm
B	16 mm
rs min	1 mm
Radial clearance class	C2
Mass	0.2 kg
Dynamic load, C	19.5 kN
Static load, C0	11.3 kN
Fatigue limit load, Cu	0.51 kN
f0	13.8
Nlim (grease)	11,000 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.4 Hz
Characteristic rolling element frequency, BSF	4.68 Hz
Characteristic outer ring frequency, BPF0	3.58 Hz
Characteristic inner ring frequency, BRFI	5.42 Hz
da min	35 mm
Da max	57 mm
ra max	1 mm

Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.198
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C2-Snug
Inch – Metric	Metric
Long Description	30MM Bore; 62MM Outside Diameter; 16MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO
Other Features	Deep Groove Prelubricated
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.439
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	0.63 Inch 16 Millimeter
Bore	1.181 Inch 30 Millimeter
Outside Diameter	2.441 Inch 62 Millimeter