

SKF LUCF 50 linear bearings

SKF LUCF 50 linear bearings 85.001 mm Da Engineering 28.804 mm Ca Calculator , Manufacturing Service . Get Your Free. 34.925 mm da

da	34.925 mm
Da	85.001 mm
Ca	28.804 mm
A1	60.325 mm
A2	88.9 mm
S	2.778 mm
ba	24.606 mm
H	112.713 mm
H1	57.15 mm
H2	20.637 mm
J min.	158.75 mm
J max.	177.8 mm
L	209.55 mm
N1	15.875 mm
R1	28.575 mm
R2	12.7 mm
RG	1/8 NPT
PG	1/8 NPT
h	24.606 mm
Housing	SAF 509
Bearing	22209 EK
Adapter sleeve assembly	SNW 9×1.3/8
Stabilizing ring	SR-9-9

Labyrinth ring	2 x LER 16
End plug (suffix Y)	EPR 3
Bearing limiting speed	10000 r/min
P60°	20.9 kN
P90°	12.5 kN
P120°	7.56 kN
P150°	6.67 kN
P180°	8.01 kN
Pa	3.09 kN
Mass pillow block	5.28 kg
Cap bolt	2 x 7/16-14 UNC
Cap bolt recommended tightening torque	61 N·m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.5 in
Initial grease fill	25.515 g