

SKF NCF2930CV cylindrical roller bearings

Manufacturers of all are represented in our partial list of clients. Contact Gary for a complete SKF NCF2930CV cylindrical roller bearings list of clients 60 mm d and projects.

| | |
|---|-----------|
| d | 60 mm |
| D | 130 mm |
| B | 31 mm |
| E | 113 mm |
| F | 77 mm |
| d1 | 84.2 mm |
| rs min | 2.1 mm |
| rls min | 2.1 mm |
| Radial clearance class | C3 |
| Mass (without HJ ring) | 1.87 kg |
| Dynamic load, C | 124 kN |
| Static load, C0 | 126 kN |
| Fatigue limit load, Cu | 15.4 kN |
| Nlim (oil) | 6,500 rpm |
| Nlim (grease) | 5,500 rpm |
| Min operating temperature, Tmin | -40 °C |
| Max operating temperature, Tmax | 120 °C |
| Characteristic cage frequency, FTF | 0.4 Hz |
| Characteristic rolling element frequency, BSF | 5.09 Hz |
| Characteristic outer ring frequency, BPF0 | 4.86 Hz |
| Characteristic inner ring frequency, BRFI | 7.14 Hz |
| da min | 71 mm |

| | |
|----------------------|---------------|
| Da max | 119 mm |
| Db min | 115 mm |
| Dc max | 111 mm |
| ra max | 2 mm |
| rla max | 2 mm |
| Inventory | 0.0 |
| Manufacturer Name | NTN |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 1.866 |
| EAN | 4547359151633 |
| Product Group | B04270 |