## SKF NNCL4856CV cylindrical roller bearings

Advance SKF NNCL4856CV cylindrical roller bearings is your source for quality and accessories. shop online for home delivery or pick up in 0.0 Inventory one of our 10000 .

| Inventory                 | 0.0   |
|---------------------------|---|
| Manufacturer Name         | IPTCI BEARINGS  |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 0.771   |
| Product Group             | M06110  |
| Number of Mounting Holes  | 4   |
| Mounting Method           | Set Screw   |
| Housing Style             | 4 Bolt Square Flange Block  |
| Rolling Element           | Ball Bearing  |
| Housing Material          | Thermoplastic   |
| Expansion / Non-expansion | Non-expansion   |
| Mounting Bolts            | 7/16 Inch   |
| Relubricatable            | Yes   |
| Insert Part Number        | SUC207-22   |
| Seals                     | B Seal  |
| Housing Configuration     | 1 Piece Solid   |
| Pilot Configuration       | No Pilot  |
| Inch — Metric             | Inch  |
| Long Description          | 4 Bolt Square Flange Block;<br>1-3/8" Bore; 5.1" Bolt Circle;<br>3-5/8" Bolt Spacing; 1 Pie |

| Other Features                        | Single Row   Spherical  <br>Corrosion Resistant  <br>Stainless Steel Insert   Has<br>Slinger   Optional End C |
|---------------------------------------|---|
| UNSPSC                                | 31171501  |
| Harmonized Tariff Code                | 8483.20.40.40   |
| Noun                                  | Bearing   |
| Keyword String                        | Flanged   |
| Manufacturer Item Number              | SUCTF 207 22  |
| Weight / LBS                          | 1.7   |
| Cartridge Pilot Diameter              | 0 Inch   0 Millimeter   |
| Nominal Bolt Circle Diameter<br>Round | 5.1 Inch   130 Millimeter   |
| D                                     | 1.689 Inch   42.9 Millimeter  |
| d                                     | 1.375 Inch   34.925 Millimeter  |
| Cartridge Pilot Depth                 | 0 Inch   0 Millimeter   |
| Bolt Spacing                          | 3.625 Inch   92.08 Millimeter   |