## SKF NU 12/500 MA thrust ball bearings

Shop SKF NU 12/500 MA thrust ball bearings huge online discount inventory. 0.0 Inventory and Import machinery parts your car needs with Free Shipping and Free Extended TIMKEN Manufacturer Name Warranty.

| Inventory                 | 0.0  |
|---------------------------|--|
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 19.522   |
| EAN                       | 0883450189330                                  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | Concentric Collar                              |
| Housing Style             | 4 Bolt Pillow Block                            |
| Rolling Element           | Spherical Roller Bearing                       |
| Housing Material          | Cast Steel                                     |
| Expansion / Non-expansion | Non-expansion                                  |
| Mounting Bolts            | 3/4 Inch                                       |
| Relubricatable            | Yes  |
| Insert Part Number        | 22218  |
| Seals                     | Triple Lip Nitrile Rubber                      |
| Housing Configuration     | 1 Piece Solid                                  |
| Inch — Metric             | Inch   |
| Other Features            | Double Row   Single Collar  <br>With Set Screw |

| Long Description                 | 4 Bolt Pillow Block; 3-1/2" Bore; 3-3/4" Base to Center Height; Concentric Collar Mount; S |
|----------------------------------|--|
| UNSPSC                           | 31171511   |
| Harmonized Tariff Code           | 8483.20.40.80  |
| Noun                             | Bearing  |
| Keyword String                   | Pillow Block   |
| Manufacturer Item Number         | QAPF18A308SM   |
| Weight / LBS                     | 49   |
| В                                | 3.75 Inch   95.25 Millimeter   |
| Nominal Bolt Center to<br>Center | 10 Inch   254 Millimeter   |
| D                                | 4.03 Inch   102.362 Millimeter   |
| Bolt Spacing Maximum             | 10.875 Inch   276.225Millimeter  |
| d                                | 3.5 Inch   88.9 Millimeter   |
| Actual Bolt Center to<br>Center  | 0 Inch   OMillimeter   |
| Bolt Spacing Minimum             | 8.875 Inch   225.425Millimeter   |