

SKF NU 2312 ECM thrust ball bearings

SKF NU 2312 ECM thrust ball bearings with easy-to-use 6 Days or more Days to Ship parts graphics, giving you the ability to check parts availability, pricing, examine remanufactured options.

Days to Ship	6 Days or more
RoHS	6
Materials of Inner and Outer Ring	Steel
Bearing Style	Double Shielded
Outer Ring Type	Flat
d	6
Outer Diameter D(Ø)	10
B	3
Basic Load Rating Dynamic Rating(N)	495
Revolution Frequency(rpm)	45000
Rolling Element Material	Steel
Basic Load Rating Static Rating(N)	218
Sealing Structure	Double steel plate shield
Lubricant	NS Hairyu-bu Grease
Bearing Ring Shape	Ball
Precision	Grade 0
Specifications/Environment	Standard
Load Direction	Radial
Number of Bearing Ring Rows	Single Row
Size Standard	Metric System
Internal Clearance Symbol	MC3

Inner/Outer Ring Material	[Steel] Steel
Outer Ring Shape	Flat
I.D.(Ø)	6
O.D.(Ø)	10
Width(mm)	3
Basic Dynamic Load Rating(N)	495
Max. Allowed rpm(rpm)	45000
Retainer Type	Punching
Basic Load Rating, Static Rating(N)	218
Clearance sign	CN (standard)
Accuracy(Class)	Class 0
Acoustic Symbol	No
Holder Symbol	No
Symbol of Bearing Ring Shape	No
Seal, Shield Symbols	ZZ1
Precision Grade Symbol	No
Special Configurations Code	No
Rubugado Symbol	No
Material Symbol	No
Spacer, Sleeve symbol	No
Types	No
Type	Ball
Specifications, Environment	Standard
Outer Ring	With Outer Ring
Number of Raceway Ring Rows	Single Row
Size Standards	Metric System
Combination symbol	No
Low Torque Specification	No
Internal Symbol	No

Torque Symbol	No
---------------	----