

SKF PCM 242720 E plain bearings

Manufacturers of 112.713 mm da 89.789 mm Ca all are represented in our partial list of clients. Contact Gary for a complete SKF PCM 242720 E plain bearings list of 230 mm Da clients and projects.

da	112.713 mm
Da	230 mm
Ca	89.789 mm
A1	133.35 mm
A2	269.875 mm
S	4.763 mm
ba	65.881 mm
H	295.275 mm
H1	152.4 mm
H2	60.325 mm
J min.	371.475 mm
J max.	406.4 mm
J1	82.55 mm
L	466.725 mm
N1	25.4 mm
R1	79.375 mm
R2	36.513 mm
RG	1/2 NPT
PG	1/4 NPT
h	60.325 mm
Housing	SAW 526

Bearing	23226 CCK/W33
Adapter sleeve assembly	SNW 126×4.7/16
Stabilizing ring	SR-26-0
Taconite seal	TER 117
End plug (suffix Y)	EPR 15
Max. speed for Taconite seal	700 r/min
P60°	189 kN
P90°	113 kN
P120°	73.8 kN
P150°	68.1 kN
P180°	84.5 kN
Pa	31.2 kN
Mass pillow block	68 kg
Cap bolt	2 x 1-8 UNC
Cap bolt recommended tightening torque	400 N·m
Cap bolt, SAE grade	5
Eye bolt	3/8-16 UNC
Appropriate attachment bolt size G	0.875 in
Initial grease fill	382.73 g