

SKF PCM 505530 M plain bearings

How 72x30x19 Size (mm) do I place an EMERGENCY order for a SKF PCM 505530 M plain bearings that I want to pick up at a our store?

Size (mm)	72x30x19
Bore Diameter (mm)	72
Outer Diameter (mm)	30
Width (mm)	19
d	30 mm
D	72 mm
B	19 mm
d1	44.6 mm
D2	61.88 mm
r1,2 – min.	1.1 mm
da – min.	37 mm
da – max.	44.5 mm
Da – max.	65 mm
ra – max.	1 mm
Basic dynamic load rating – C	29.6 kN
Basic static load rating – C0	16 kN
Fatigue load limit – Pu	0.67 kN
Reference speed	20000 r/min
Limiting speed	13000 r/min
Calculation factor – kr	0.03
Calculation factor – f0	13.1
Inventory	0.0

Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.357
EAN	7316577654595
Product Group	B00308
Enclosure	1 Metal Shield
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	30MM Bore; 72MM Outside Diameter; 19MM Outer Race Diameter; 1 Metal Shield; Ball Bearing; ABEC 1 I
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6306-Z
Weight / LBS	0.8
Outside Diameter	2.835 Inch 72 Millimeter
Bore	1.181 Inch 30 Millimeter
Outer Race Width	0.748 Inch 19 Millimeter
d1 ≈	44.6 mm
D2 ≈	61.88 mm
r1,2 min.	1.1 mm

da min.	37 mm
da max.	44.5 mm
Da max.	65 mm
ra max.	1 mm
Basic dynamic load rating C	29.6 kN
Basic static load rating C ₀	16 kN
Fatigue load limit P _u	0.67 kN
Calculation factor k _r	0.03
Calculation factor f ₀	13.1
Mass bearing	0.35 kg