

SKF PCM 758040 M plain bearings

Shop 20 mm d 47 mm D SKF PCM 758040 M plain bearings huge online discount inventory. and Import machinery parts your car needs with Free Shipping and Free Extended 14 mm B Warranty.

d	20 mm
D	47 mm
B	14 mm
rs min	1 mm
Radial clearance class	C3
Mass	0.11 kg
Dynamic load, C	12.8 kN
Static load, C0	6.65 kN
Fatigue limit load, Cu	0.3 kN
f0	13.2
Nlim (grease)	10,000 rpm
Min operating temperature, Tmin	-10 °C
Max operating temperature, Tmax	150 °C
Characteristic cage frequency, FTF	0.38 Hz
Characteristic rolling element frequency, BSF	4.12 Hz
Characteristic outer ring frequency, BPF0	3.08 Hz
Characteristic inner ring frequency, BRFI	4.92 Hz
da min	25 mm
da max	28 mm

Da max	42 mm
ra max	1 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.106
Product Group	B04270
Enclosure	2 Seals
Precision Class	ABEC 3 ISO P6
Material – Ball	Steel
Number of Bearings	1 (Single)
Contact Angle	0 Degree
Preload	None
Raceway Style	Not Applicable
Cage Material	Steel
Rolling Element	Ball Bearing
Enclosure Type	Contact Seal
Flush Ground	No
Inch – Metric	Metric
Other Features	Single Row Deep Groove C3 Clearance Prelubricant
Long Description	20MM Bore; 47MM Outside Diameter; 14MM Width; 2 Seals Enclosure; ABEC 3 ISO P6 Precision; Steel Ba
UNSPSC	31171502
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball Deep Groove
Bore	0.787 Inch 20 Millimeter

Width	0.551 Inch 14 Millimeter
Outside Diameter	1.85 Inch 47 Millimeter