

SKF PCM 758080 M plain bearings

SKF PCM 758080 M plain bearings with easy-to-use parts graphics, giving you 150.813 mm da the ability to check parts availability, 309.999 mm Da pricing, examine remanufactured options.

da	150.813 mm
Da	309.999 mm
Ca	95.809 mm
A1	171.45 mm
A2	309.563 mm
S	4.763 mm
ba	74.612 mm
H	360.363 mm
H1	179.4 mm
H2	69.85 mm
J min.	492.125 mm
J max.	549.275 mm
J1	107.95 mm
L	628.65 mm
N1	28.575 mm
R1	115.888 mm
R2	37.306 mm
RG	3/4 NPT
PG	1/4 NPT
h	54.769 mm
Housing	SAFS 534

Bearing	22234 CCK/W33
Adapter sleeve assembly	SNW 34×5.15/16
Stabilizing ring	SR-34-0
Taconite seal	TER 140
End plug (suffix Y)	EPR 18
Max. speed for Taconite seal	520 r/min
P60°	345 kN
P90°	207 kN
P120°	127 kN
P150°	113 kN
P180°	133 kN
Pa	43.6 kN
Mass pillow block	165 kg
Cap bolt	1-8 UNC
Cap bolt recommended tightening torque	1220 N·m
Cap bolt, SAE grade	8
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1 in
Initial grease fill	878.85 g